



OIL&AIR VALUE

FORK (Torco RFF 10wt for Damper / XF Pure Slick Fluid for air spring/lower)

Model		Damper Oil(c.c)	Air Oil(c.c)	Lower leg Oil(c.c)
SLIDE X32	RL	140	10	15/per leg
	R	125		
VELVET	RL/R	70		
	RL(C-Style)	140		
SLANT SWEEP TRACE McQueen E-SLIDE	RC	N/A		
	RC HLR	bleed		
	RL/R	70		
	RL (closed)	50		
VENGEANCE	HLR/RC	85		20/per leg
	R	fill		
TRACE36 METRIC RV-1	HLR/RC	100		
	RC HLR	bleed		
	R	Damper oil:fill IFP Depth:110mm air presure:50psi		
REVEL-X	RC HLR	bleed		30(fill from left crown)

SHOCK (use Torco Medium RSF 10wt)

Model	Damper Oil(c.c)	Air sleeve Oil(c.c)
Microlite series	fill	5
O2/O2 pro series		
Stage series		
Vector series		

HILO(use Mobil Multipurpose ATF Oil 7.5wt)

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)
27.2	100	65	28
30.9	100	70	18
31.6	100	70	18
30.9	125	78	18
31.6	125	78	18

HILO SL(use Mobil Multipurpose ATF Oil 7.5wt)

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)
30.9	125	90	14
31.6			

HILO SLS(use Torco Lite RFF 7.5wt)

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)	IFP Deepth(mm)
30.9	125	fill	35	15
31.6	150			